




# [ Products ] you can identify with



Physical Specifications		
Material	ABS Rigid Plastic	
Size	80 x 15 x 12.5 mm, 3.15 x 0.59 x 0.48 in	
Weight (g)	12.5	
Attachment	Mechanical (std), cable tie or premium foam (option)	

#### **Dimensions**



Measurements shown in mm


### Exo 600

Omni-ID Exo 600 is a small, high performance, global RFID tag designed to meet the diverse needs of logistics industries. With a small footprint it is well suited for attachment to metal bars commonly found on RTI's. Exo 600 has a long read range and broad read angle for industrial and warehouse portal applications and is easily mounted using rivets or closed cell foam adhesive.

RF Specifications			
Radio Protocol	EPC Class 1 Gen2v2		
Frequency Range	860 - 930 (GS)		
Read Range - Fixed Reader	Up to 6m (on metal), Up to 4m (off metal)		
Read Range - Handheld Reader	Up to 3m (on metal)		
On Metal or Balanced	Optimized for metal		
IC Type (Chip)	Impinj Monza 4QT		
Memory	EPC - 128 bits User - 512 bits Unique TID - 48 bits		

EPC and User memory are reprogrammable. UTID is locked at point of manufacture by IC manufacturer.

#### **Radiation Patterns**







## [ Products ] you can identify with



With a small footprint and high performance, Exo 600 is ideally suited for RTI applications in the following industries:

- Logistics and Postal
- Retail and Warehousing

#### Certifications

CE, RoHS, ATEX/IECEx certified (option), US&Canada (C1D1/D2) certified (option)





Environmental Specifications		
Operating Temperature	-40°C to +85°C	
Survivability	-40°C to +85°C	
IP Rating	IP68	
Shock & Vibration Tolerance	MIL-STD-810 G	
Impact	10KG from 1m	

Ordering Information			
Warranty	3 years		
Product Options	:303 (Customization) :304 (ATEX/IECEx certified) :307 (US&Canada (C1D1/D2) certified) :332 (Transparent case) :508 (Premium foam) :701 (Standard Service Bureau)		
Part Number / Order Codes / Order Numbers	061 - (GS)		